

MF17251



Size : 172 x 150 x 51 mm (6.77 x 5.91 x 2.01 inch)
 Motor : Shaded Pole
 Frame : Aluminum Die-Cast
 Impeller : PBT + 30% Fiber Glass. UL94V-0
 Lead Wire : 1007# 18AWG. UL/CSA
 Insulation Resistance :
 Min 10 M Ohm at 500VDC Between Terminal and the Frame
 Dielectric Strength : 1 min at 1,500VAC 50/60Hz
 Bearing Type : B: 2 Ball Bearing. S: Sleeve Bearing
 Operating Temp : Ball Bearing: Within -20 ~ 80°C
 Sleeve Bearing: Within -10 ~ 56°C
 Life Expectancy : Ball Bearing: 50,000 hours at 60C
 Sleeve Bearing: 20,000 hours at 45°C
 Net Weight : 920 grams

172x150x51mm

Fan guard corresponding model			
Metal	Plastic	Plastic filter	Ventilator Filter
FG-172	FF-172	FS-172	MA-06

Part No.	Bearing system	Rated Voltage (V)	Freg (Hz)	Current (A)	Input Power (W)	Speed (rpm)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise Level (dB-A)	Weight (g)
17251A1HSAT(L) 17251A1HBAT(L)	Sleeve Ball	110/120	50/60	0.55/0.48	45/52	2800/3100	190/220	0.55/0.72	53/59	920
17251A2HSAT(L) 17251A2HBAT(L)	Sleeve Ball	220/240	50/60	0.35/0.28	45/52	2800/3100	190/220	0.55/0.72	53/59	920
17251A3HBAT(L)	Ball	380	50/60	0.05/0.04	19/15	2600/2300	170/145	0.43/0.18	53/59	920
		415		0.09/0.10	37/42	2600/2700	170/185	0.43/0.41		
17251DVH (Dual Voltage)	Sleeve Ball	110/120	50/60	0.55/0.48	45/52	2800/3100	190/220	0.55/0.72	53/59	920
		220/240		0.35/0.28	45/52	2800/3100	190/220	0.55/0.72		

Specifications subject to change without notice.

