

MFB12032



Size : 120 x 120 x 32 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 220 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maimun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB12032D1-L	12	6.0 ~ 13.5	0.5	6	2500	26.5	20.25	48.2
MFB12032D1-M			0.65	7.8	3000	31.9	27.47	51.9
MFB12032D1-H			1.7	20.1	3500	36.9	35.92	55.6
MFB12032D1-HH			2.2	26.4	4000	41.9	48.47	59.9
MFB12032D2-L	24	18 ~ 26.5	0.25	6	2500	26.5	20.25	48.2
MFB12032D2-M			0.33	8	3000	31.9	27.47	51.9
MFB12032D2-H			0.55	13.2	3500	36.9	35.92	55.6
MFB12032D2-HH			1.1	26.4	4000	41.9	48.47	59.9
MFB12032D4-L	48	36 ~ 55	0.13	6	2500	26.5	20.25	48.2
MFB12032D4-M			0.28	13.2	3000	31.9	27.47	51.9
MFB12032D4-H			0.42	20.1	3500	36.9	35.92	55.6
MFB12032D4-HH			0.55	26.4	4000	41.9	48.47	59.9

DIMENSIONS DRAWING & P&Q CURVE

