

MFB3507



Size : 30 x 30 x 10 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 10 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maimun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB3507D05-L	5	1.8 ~ 6.8	0.08	0.4	5000	0.84	4.08	23.9
MFB3507D05-M			0.12	0.6	6000	1.11	5.92	27.2
MFB3507D05-H			0.18	0.9	7500	1.39	9.84	32.3
MFB3507D1-L	12	7.0 ~ 13.5	0.034	0.4	5000	0.84	4.08	23.9
MFB3507D1-M			0.05	0.6	6000	1.11	5.92	27.2
MFB3507D1-H			0.075	0.9	7500	1.39	9.84	32.3

DIMENSIONS DRAWING & P&Q CURVE

