

MFB4015



Size : 40 x 40 x 15 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 13 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB4015D05-LL	5	1.8 ~ 6.8	0.07	0.38	5000.00	1.37	3.42	29.00
MFB4015D05-L			0.09	0.48	6000.00	1.64	5.25	33.50
MFB4015D05-M			0.12	0.60	7000.00	1.97	7.15	37.60
MFB4015D05-H			0.17	0.84	8000.00	2.39	10.58	41.20
MFB4015D05HH			0.22	1.08	9000.00	2.70	13.70	44.70
MFB4015D05-VH			0.31	1.56	10000.00	2.95	17.70	47.00
MFB4015D05-HV			0.35	1.80	11000.00	3.33	25.57	49.40
MFB4015D1-LL	12	7.0 ~ 13.5	0.03	0.38	4000.00	1.37	3.42	29.00
MFB4015D1-L			0.04	0.48	5000.00	1.64	5.25	33.50
MFB4015D1-M			0.05	0.60	6000.00	1.97	7.15	37.60
MFB4015D1-H			0.07	0.84	7000.00	2.39	10.58	41.20
MFB4015D1-HH			0.09	1.08	8000.00	2.70	13.70	44.70
MFB4015D1-VH			0.13	1.56	9000.00	2.95	17.70	47.00
MFB4015D1-HV			0.15	1.80	11000.00	3.33	25.57	49.40

DIMENSIONS DRAWING & P&Q CURVE

