

MFB4020



Size : 40 x 40 x 20 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 30 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage VDC	Operating Voltage Range VDC	Rated Current Amp	Rated Input Power Watt	Speed R.P.M	Maximun Air Flow CFM	Maimun Air Pressure mmH2O	Noise DB-A
MFB4020D05-LL	5	3.6 ~ 6.8	0.14	0.72	4500.00	2.00	2.64	27.40
MFB4020D05-L			0.16	0.80	5000.00	2.27	3.35	30.20
MFB4020D05-ML			0.24	1.20	5500.00	2.56	4.18	33.50
MFB4020D05-LM			0.29	1.44	6000.00	2.75	5.22	35.70
MFB4020D05-M			0.34	1.68	6500.00	3.06	6.55	37.40
MFB4020D05-H			0.38	1.92	7500.00	3.54	9.13	40.90
MFB4020D1-LL	12	6.0 ~ 13.5	0.06	0.72	4500.00	2.00	2.64	27.40
MFB4020D1-L			0.07	0.80	5000.00	2.27	3.35	30.20
MFB4020D1-ML			0.10	1.20	5500.00	2.56	4.18	33.50
MFB4020D1-LM			0.12	1.44	6000.00	2.75	5.22	35.70
MFB4020D1-M			0.14	1.68	6500.00	3.06	6.55	37.40
MFB4020D1-H			0.16	1.92	7500.00	3.54	9.13	40.90
MFB4020D1-HH			0.18	2.16	8500.00	4.00	12.16	44.50
MFB4020D2-LL	24	18 ~ 26.5	0.03	0.72	4500.00	2.00	2.64	27.40
MFB4020D2-ML			0.05	1.20	5500.00	2.56	4.18	33.50
MFB4020D2-LM			0.06	1.44	6000.00	2.75	5.22	35.70
MFB4020D2-M			0.07	1.68	6500.00	3.06	6.55	37.40
MFB4020D2-H			0.08	1.92	7500.00	3.54	9.13	40.90
MFB4020D2-HH			0.09	2.16	8500.00	4.00	12.16	44.50

DIMENSIONS DRAWING & P&Q CURVE

