

MFB4510



Size : 45 x 45 x 10 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 30 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH ₂ O	DB-A
MFB4510D05-L	5	3.6 ~ 6.8	0.11	0.55	3500.00	1.66	3.11	21.50
MFB4510D05-M			0.14	0.70	4500.00	2.15	5.78	27.00
MFB4510D05-H			0.17	0.85	5500.00	2.75	9.72	30.50
MFB4510D05-HH			0.20	1.00	6500.00	3.28	14.09	35.50
MFB4510D1-L	12	6.0 ~ 13.5	0.05	0.60	3500.00	1.66	3.11	21.50
MFB4510D1-M			0.07	0.84	4500.00	2.15	5.78	27.00
MFB4510D1-H			0.09	1.08	5500.00	2.75	9.72	30.50
MFB4510D1-HH			0.11	1.32	6500.00	3.28	14.09	35.50

DIMENSIONS DRAWING & P&Q CURVE

