

MFB6015



Size : 60 x 60 x 15 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 65 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB6015D1-L	12	6.0 ~ 13.5	0.02	0.20	2500.00	2.24	3.31	24.40
MFB6015D1-M			0.04	0.40	3000.00	2.78	5.12	29.50
MFB6015D1-H			0.06	0.70	3500.00	3.16	7.13	33.60
MFB6015D1-HH			0.08	1.00	4000.00	3.67	9.72	36.90
MFB6015D1-VH			0.10	1.20	4500.00	4.13	12.70	40.50
MFB6015D1-HV			0.13	1.60	5000.00	4.54	16.62	43.50
MFB6015D2-L	24	18 ~ 26.5	0.01	0.20	2500.00	2.24	3.31	24.40
MFB6015D2-M			0.02	0.48	3000.00	2.78	5.12	29.50
MFB6015D2-H			0.03	0.70	3500.00	3.16	7.13	33.60
MFB6015D2-HH			0.04	1.00	4000.00	3.67	9.72	36.90
MFB6015D2-VH			0.05	1.20	4500.00	4.13	12.70	40.50
MFB6015D1-HV			0.07	1.60	5000.00	4.54	16.62	43.50

DIMENSIONS DRAWING & P&Q CURVE

