

MFB6025



Size : 60 x 60 x 25 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 70 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB6025D05-H	5	3.6 ~ 6.8	0.24	1.20	3200.00	6.71	10.88	34.00
MFB6025D05-H			0.28	1.40	3700.00	7.88	15.49	39.00
MFB6025D1-M	12	6.0 ~ 13.5	0.10	1.20	3200.00	6.71	10.88	34.00
MFB6025D1-H			0.12	1.44	3700.00	7.88	15.49	39.00
MFB6025D2-M	24	18 ~ 26.5	0.05	1.20	3200.00	6.71	10.88	34.00
MFB6025D2-H			0.06	1.50	3700.00	7.88	15.49	39.00

DIMENSIONS DRAWING & P&Q CURVE

