

MFB6028



Size : 60 x 60 x 28 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 70 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maimun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB6028D05-L	5	3.6 ~ 6.8	0.14	0.72	3000.00	3.79	3.91	29.40
MFB6028D05-M			0.19	0.96	3500.00	4.25	5.54	32.60
MFB6028D05-H			0.24	1.20	4000.00	4.94	7.79	36.60
MFB6028D05-HH			0.34	1.66	4500.00	5.52	10.29	38.80
MFB6028D05-VH			0.43	2.16	5000.00	6.32	13.75	41.30
MFB6028D05-HV			0.48	2.40	5500.00	6.99	17.67	44.30
MFB6028D1-L	12	6.0 ~ 13.5	0.05	0.72	3000.00	3.79	3.91	29.40
MFB6028D1-M			0.08	0.96	3500.00	4.25	5.54	32.60
MFB6028D1-H			0.10	1.20	4000.00	4.94	7.79	36.60
MFB6028D1-HH			0.14	1.68	4500.00	5.52	10.29	38.80
MFB6028D1-VH			0.18	2.18	5000.00	6.32	13.75	41.30
MFB6028D1-HV			0.20	2.40	5500.00	6.99	17.67	44.30
MFB6028D2-L	24	18 ~ 26.5	0.03	0.72	3000.00	3.79	3.91	29.40
MFB6028D2-M			0.04	0.96	3500.00	4.25	5.54	32.60
MFB6028D2-H			0.05	1.20	4000.00	4.94	7.79	36.60
MFB6028D2-HH			0.07	1.68	4500.00	5.52	10.29	38.80
MFB6028D2-VH			0.09	2.16	5000.00	6.32	13.75	41.30
MFB6028D2-HV			0.10	2.40	5500.00	6.99	17.67	44.30

DIMENSIONS DRAWING & P&Q CURVE

