

MFB7015



Size : 70 x 70 x 15 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 72 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maimun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB7015D1-L	12	6.0 ~ 13.5	0.10	1.20	2000.00	4.20	5.29	30.20
MFB7015D1-M			0.14	1.62	2500.00	5.18	9.30	35.70
MFB7015D1-H			0.16	1.92	3000.00	6.27	13.81	39.60
MFB7015D1-HH			0.18	2.20	3500.00	7.21	20.66	44.40
MFB7015D2-L	24	18 ~ 26.5	0.05	1.20	2000.00	4.20	5.29	30.20
MFB7015D2-M			0.07	1.62	2500.00	5.18	9.30	35.70
MFB7015D2-H			0.08	2.00	3000.00	6.27	13.81	39.60
MFB7015D2-HH			0.10	2.40	3500.00	7.21	20.66	44.40

DIMENSIONS DRAWING & P&Q CURVE

