

MFB7530



Size : 75 x 75 x 30 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL: 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 80 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maimun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFB7530D1-L	12	6.0 ~ 13.5	0.16	1.92	2000.00	6.37	2.65	33.20
MFB7530D1-M			0.26	3.12	2500.00	8.87	5.53	37.50
MFB7530D1-H			0.34	4.08	3000.00	9.25	7.26	42.70
MFB7530D1-HH			0.46	5.52	3500.00	10.80	11.25	45.60
MFB7530D1-VH			0.60	7.20	4000.00	12.90	14.37	46.80
MFB7530D2-L	24	18 ~ 26.5	0.08	1.92	2000.00	6.37	2.65	33.20
MFB7530D2-M			0.13	3.12	2500.00	8.87	5.53	37.50
MFB7530D2-H			0.17	4.08	3000.00	9.25	7.26	42.70
MFB7530D2-HH			0.23	5.52	3500.00	10.80	11.25	45.60
MFB7530D2-VH			0.30	7.20	4000.00	12.90	14.37	46.80
MFB7530D4-L	48	36 ~ 55	0.04	1.92	2000.00	6.37	2.65	33.20
MFB7530D4-M			0.07	3.12	2500.00	8.87	5.53	37.50
MFB7530D4-H			0.09	4.08	3000.00	9.25	7.26	42.70
MFB7530D4-HH			0.12	5.52	3500.00	10.80	11.25	45.60
MFB7530D4-VH			0.15	7.20	4000.00	12.90	14.37	46.80

DIMENSIONS DRAWING & P&Q CURVE

