

MFD14038B



Size : 140 x 140 x 38mm
 Bearing system: BALL
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Weight: 180 g

Bearing system

BALL	SLEEVE
●	

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL PART NO.	Rated Voltage VDC	Operating Voltage Range VDC	Rated Current Amp	Rated Input Power Watt	Speed R.P.M	Maximum Air Flow CFM	Maximum Air Pressure mmH ₂ O	Noise DB-A
MFD14038BD1-L	12	7.5 ~ 13.5	2.3	27	4500	167.7	17.92	55.8
MFD14038BD1-M			2.5	30	5000	189.71	22.4	58.2
MFD14038BD1-H			2.7	32	5500	209.4	26.72	62
MFD14038BD1-HH			3	36	6000	229.45	31.64	64
MFD14038BD1-VH			3.5	42	6500	254.89	37.93	67.8
MFD14038BD2-L	24	18 ~ 26.5	1.17	28	4500	167.7	17.92	55.8
MFD14038BD2-M			1.33	32	5000	189.71	22.4	58.2
MFD14038BD2-H			1.42	34	5500	209.4	26.72	62
MFD14038BD2-HH			1.58	38	6000	229.45	31.64	64
MFD14038BD2-VH			1.83	44	6500	254.89	37.93	67.8
MFD14038BD4-L	48	36 ~ 54	0.63	30	4500	167.7	17.92	55.8
MFD14038BD4-M			0.71	34	5000	189.71	22.4	58.2
MFD14038BD4-H			0.79	38	5500	209.4	26.72	62
MFD14038BD4-HH			0.92	44	6000	229.45	31.64	64
MFD14038BD4-VH			1.04	50	6500	254.89	37.93	67.8

DIMENSIONS DRAWING & P&Q CURVE

