

MFD22060



Size : $\varnothing 220 \times 60$ mm
 Bearing system: BALL
 Frame: Aluminum
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: $-10 \sim 70^{\circ}\text{C}$
 Sleeve: $-10 \sim 70^{\circ}\text{C}$
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Weight: 1150 g

Bearing system

BALL	SLEEVE
●	

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD22060D1-M	12	7~ 13.5	1.65	19.8	2000	400.58	6.65	54.6
MFD22060D1-H			2.92	35.04	2500	513.39	12.15	60
MFD22060D1-HH			4.73	56.76	3000	586.69	17.28	63.6
MFD22060D1-VH			7.4	88.8	3500	645.61	22.02	68.5
MFD22060D2-M	24	18 ~26.5	0.78	18.81	2000	400.58	6.65	54.6
MFD22060D2-H			1.39	33.29	2500	513.39	12.15	60
MFD22060D2-HH			2.25	53.92	3000	586.69	17.28	63.6
MFD22060D2-VH			3.52	84.36	3500	645.61	22.02	68.5
MFD22060D4-M	48	36 ~54	0.37	17.87	2000	400.58	6.65	54.6
MFD22060D4-H			0.66	31.62	2500	513.39	12.15	60
MFD22060D4-HH			1.07	51.23	3000	586.69	17.28	63.6
MFD22060D4-VH			1.67	80.14	3500	645.61	22.02	68.5

DIMENSIONS DRAWING & P&Q CURVE

