

MFD2507



Size : 25 x 25 x 7 mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 5 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD2507D05-L	5	3.6 ~ 6.8	0.06	0.3	7000	1.22	2.16	19.6
MFD2507D05-M			0.09	0.45	10000	1.55	3.1	23.5
MFD2507D05-H			0.23	1.15	14000	1.9	3.8	26.4
MFD2507D05-HH			0.28	1.4	17000	2.81	4.5	31.2
MFD2507D1-L	12	6.0 ~ 13.5	0.03	0.3	7000	1.22	2.16	19.6
MFD2507D1-M			0.04	0.45	10000	1.55	3.1	23.5
MFD2507D1-H			0.1	1.15	14000	1.9	3.8	26.4
MFD2507D1-HH			0.12	1.44	17000	2.81	4.5	31.2

DIMENSIONS DRAWING & P&Q CURVE

