

MFD2510



Size : 25 x 25 x 10 mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 7 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD2510D05-L	5	3.6 ~ 6.8	0.15	0.55	8500	1.01	1.86	17.8
MFD2510D05-M			0.17	0.85	10500	1.44	3.24	27.2
MFD2510D05-H			0.19	1.15	12000	1.72	3.88	28.9
MFD2510D05-HH			0.22	1.5	13500	2.35	6.87	32.9
MFD2510D05-VH			0.24	1.2	16000	2.63	8.73	37.6
MFD2510D1-L	12	6.0 ~ 13.5	0.06	0.36	8500	1.01	1.86	17.8
MFD2510D1-M			0.07	0.72	10500	1.44	3.24	27.2
MFD2510D1-H			0.08	1.08	12000	1.72	3.88	28.9
MFD2510D1-HH			0.09	1.08	13500	2.35	6.87	32.9
MFD2510D1-VH			0.1	1.2	16000	2.63	8.73	37.6

DIMENSIONS DRAWING & P&Q CURVE

