

MFD4015



Size : 40 x 40 x 15mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 25 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL PART NO.	Rated Voltage VDC	Operating Voltage Range VDC	Rated Current Amp	Rated Input Power Watt	Output Speed R.P.M	Maximum Air Flow CFM	Maximum Air Pressure mm H ₂ O	Noise DB - A
MFD4015D05-I	5	1.8 ~ 6	0.08	0.75	5000	6.5	3.67	18.5
MFD4015D05-LM			0.22	1.1	6000	8.12	5.12	24.5
MFD4015D05-M			0.24	1.2	7000	9.46	6.92	28.5
MFD4015D05-F			0.32	1.6	8300	11.48	9.13	32
MFD4015D05-FH			0.38	1.9	9500	13	11.66	36.5
MFD4015D1-L	12	7.5 ~ 13.5	0.04	0.72	5000	6.5	3.67	18.5
MFD4015D1-LM			0.05	1.08	6000	8.12	5.12	24.5
MFD4015D1-M			0.07	1.2	7000	9.46	8.92	28.5
MFD4015D1-H			0.13	1.56	8300	11.48	9.13	32
MFD4015D1-HH			0.16	1.92	9500	13	11.66	36.5
MFD4015D1-VH	0.25	3	11000	14.83	15.26	41.5		
MFD4015D2-L	24	18 ~ 26.5	0.05	1.2	5000	6.5	3.67	18.5
MFD4015D2-LM			0.06	1.44	6000	8.12	5.12	24.5
MFD4015D2-M			0.08	1.92	7000	9.46	6.92	28.5
MFD4015D2-H			0.09	2.16	8300	11.48	9.13	32
MFD4015D2-HH			0.1	2.4	9500	13	11.66	36.5
MFD4015D2-VH	0.12	2.88	11000	14.83	15.26	41.5		

DIMENSIONS DRAWING & P&Q CURVE

