

MFD6010



Size : 60 x 60 x 10mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 21 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD6010D05-L	5	1.8~6	0.12	0.6	3000	11.4	1.3	25.3
MFD6010D05-M			0.19	0.95	3500	13.4	1.67	29.3
MFD6010D05-H			0.26	1.32	4000	16.2	2.29	32.8
MFD6010D05-HH			0.34	1.68	4500	17.7	2.72	35.9
MFD6010D05-VH			0.43	2.04	5000	19.4	3.34	39
MFD6010D1-L	12	8.5~13.5	0.05	0.6	3000	11.4	1.3	25.3
MFD6010D1-M			0.08	0.95	3500	13.4	1.67	29.3
MFD6010D1-H			0.11	1.32	4000	16.2	2.29	32.8
MFD6010D1-HH			0.14	1.68	4500	17.7	2.72	35.9
MFD6010D1-VH			0.17	2.04	5000	19.4	3.34	39

DIMENSIONS DRAWING & P&Q CURVE

