

MFD6010B



Size : 60 x 60 x 10mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 21 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD6010BD05-L	5	1.8~6	0.072	0.36	3000	11.6	1.48	21
MFD6010BD05-M			0.096	0.48	3500	13.7	1.83	24.4
MFD6010BD05-H			0.12	0.6	4000	15.9	2.43	29.5
MFD6010BD05-HH			0.144	0.72	4500	17.7	2.95	30.5
MFD6010BD05-VH			0.168	0.84	5000	19.3	3.56	34.4
MFD6010BD1-L	12	8.5~13.5	0.03	0.36	3000	11.6	1.48	21
MFD6010BD1-M			0.04	0.48	3500	13.7	1.83	24.4
MFD6010BD1-H			0.05	0.6	4000	15.9	2.43	29.5
MFD6010BD1-HH			0.06	0.72	4500	17.7	2.95	30.5
MFD6010BD1-VH			0.07	0.84	5000	19.3	3.56	34.4

DIMENSIONS DRAWING & P&Q CURVE

