

MFD6025



Size : 60 x 60 x 25mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 60 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Inp Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH ₂ O	DB-A
MFD6025D1-L	12	8.5 ~ 13.5	0.06	0.72	3000	15.7	2.13	27.2
MFD6025D1-LM			0.14	1.68	3500	18.9	2.76	30.7
MFD6025D1-M			0.17	2.04	4000	21.5	3.64	34.3
MFD6025D1-H			0.2	2.4	4500	24.3	4.63	37.7
MFD6025D1-LH			0.23	2.76	5000	26.9	5.56	40.2
MFD6025D2-L	24	18 ~ 26.5	0.05	1.2	3000	15.7	2.13	27.2
MFD6025D2-LM			0.07	1.68	3500	18.9	2.76	30.7
MFD6025D2-M			0.085	2.04	4000	21.5	3.64	34.3
MFD6025D2-H			0.1	2.4	4500	24.3	4.63	37.7
MFD6025D2-LH			0.11	2.76	5000	26.9	5.56	40.2
MFD6025D4-L	48	36 ~ 54	0.025	1.2	3000	15.7	2.13	27.2
MFD6025D4-LM			0.035	1.68	3500	18.9	2.75	30.7
MFD6025D4M			0.04	2.04	4000	21.5	3.64	34.3
MFD6025D4-H			0.05	2.4	4500	24.3	4.63	37.7
MFD6025D4-LH			0.06	2.76	5000	26.9	5.56	40.2

DIMENSIONS DRAWING & P&Q CURVE

