

MFD7015



Size : 70 x 70 x 15mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 44 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD7015D05-VL	5	1.8 ~ 6	0.1	0.48	2000	13.9	0.89	22.9
MFD7015D1-VL	12	7 ~ 13.5	0.04	0.48	2500	14.8	1.36	22.9
MFD7015D1-LL			0.06	0.72	3000	19.7	2.1	27.2
MFD7015D1-L			0.08	0.96	3500	23	2.92	33.3
MFD7015D1-M			0.12	1.44	4000	26	3.55	36.2
MFD7015D1-H			0.29	3.48	4500	29.8	4.62	38.9
MFD7015D2-VL			24	18~26.5	0.02	0.48	2500	14.8
MFD7015D2-LL	0.03	0.72			3000	19.7	2.1	27.2
MFD7015D2-L	0.04	0.96			3500	23	2.92	33.3
MFD7015D2-M	0.06	1.44			4000	26	3.55	36.2
MFD7015D2-H	0.09	2.16			4500	29.8	4.62	38.9

DIMENSIONS DRAWING & P&Q CURVE

