

MFD8015



Size : 80 x 80 x 15 mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 49g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD8015D05-L	5	3.6 ~ 6.8	0.24	1.2	2000	22.8	1.2	30.4
MFD8015D1-L	12	6.0 ~ 13.5	0.1	1.2	2000	22.8	1.2	30.4
MFD8015D1-M			0.16	1.92	2500	25	1.65	33.5
MFD8015D1-H			0.2	2.4	3000	31.9	2.44	36.2
MFD8015D1-HH			0.25	3	3500	36.6	3.38	40.3
MFD8015D2-L	24	18 ~ 26.5	0.06	1.44	2000	22.8	1.2	30.4
MFD8015D2-M			0.08	1.92	2500	25	1.65	33.5
MFD8015D2-H			0.1	2.4	3000	31.9	2.44	36.2
MFD8015D2-HH			0.18	3	3500	36.6	3.38	40.3

DIMENSIONS DRAWING & P&Q CURVE

