

MFD8038B



Size : 80 x 80 x 38 mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 175 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow	Maximun Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH2O	DB-A
MFD8038BD1-VH	12	7~13.5	2.04	24.5	8500	113.31	36.43	61.9
MFD8038BD1-MVH			2.68	32.2	9500	128.01	45.21	64.7
MFD8038BD1-VVH			3	36	10000	133.95	50.02	66.6
MFD8038BD2-VH	24	18 ~ 26.5	1.02	24.5	8500	113.31	36.43	61.9
MFD8038BD2-MVH			1.34	32.2	9500	128.01	45.21	64.7
MFD8038BD2-VVH			1.5	36	10000	133.95	50.02	66.6
MFD8038BD4-VH	48	36 ~ 54	0.51	24.5	8500	113.31	36.43	61.9
MFD8038BD4-MVH			0.67	32.2	9500	128.01	45.21	64.7
MFD8038BD4-VVH			0.75	36	10000	133.95	50.02	66.6

DIMENSIONS DRAWING & P&Q CURVE

