

MFD9238



Size : 92 x 92 x 38mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 175 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	CFM	mmH ₂ O	DB-A
MFD9238D1-L	12	6.0 ~ 13.5	0.28	6	3500	70.86	8.25	48
MFD9238D1-M			0.9	10.8	4500	94.09	14.26	55.1
MFD9238D1-H			1.2	14.4	5500	112.5	20.24	64.5
MFD9238D1-HH			1.6	16.2	6500	133.04	24.87	65.6
MFD9238D1-VH			2.1	25.2	7500	144.26	30.88	66.2
MFD9238D2-L	24	18 ~ 26.5	0.25	6	3500	70.86	8.25	48
MFD9238D2-M			0.31	7.44	4500	94.09	14.26	55.1
MFD9238D2-H			0.55	13.2	5500	112.5	20.24	64.5
MFD9238D2-HH			0.8	19.2	6500	133.04	24.87	65.6
MFD9238D2-VH			1.05	25.2	7500	144.26	30.88	66.2
MFD9238D4-L	48	36 ~ 55	0.13	6	3500	70.86	8.25	48
MFD9238D4-M			0.23	10.8	4500	94.09	14.26	55.1
MFD9238D4-H			0.36	14.4	5500	112.5	20.24	64.5
MFD9238D4-HH			0.4	16.2	6500	133.04	24.87	65.6
MFD9238D4-VH			0.53	25.2	7500	144.26	30.88	66.2

DIMENSIONS DRAWING & P&Q CURVE

