

MFE8025



Size : 80x 80 x 25mm
 Bearing system: BALL, Sleeve
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 BALL: -10 ~ 70°C
 Sleeve: -10 ~ 70°C
 Life Expectancy
 Ball : 50,000 hours at 25°C
 Sleeve: 25,000 hours at 25°C
 Weight: 85 g

Bearing system

| BALL | SLEEVE |
|------|--------|
| ● | ● |

| MODEL | Rated Voltage | Operating Voltage Range | Rated Input Power | Speed | Maximum Air Flow | Maximum Air Pressure | Noise |
|------------|---------------|-------------------------|-------------------|-------|------------------|----------------------|-------|
| PART NO. | VAC | VDC | Watt | R.P.M | CFM | mmH ₂ O | DB-A |
| MFE8025-L | 220 | 80-230 | 6.6 | 2000 | 24.4 | 2 | 25.8 |
| MFE8025-M | | | 6.6 | 2500 | 31.4 | 2.8 | 29.1 |
| MFE8025-H | | | 8.8 | 3000 | 37.9 | 4 | 34.2 |
| MFE8025-HH | | | 8.8 | 3500 | 44.3 | 5.3 | 36.9 |

DIMENSIONS DRAWING & P&Q CURVE

