

MFL22599



Size : Ø 225 x 99 mm
 Bearing system: BALL, SLEEVE
 Frame: plastic PBT UL94V-0
 Impeller: plastic PBT UL94V-0
 Operating Temp :
 Sleeve: -10 ~ 70°C
 Life Expectancy
 BALL : 50,000 hours at 25°C
 SLEEVE : 25,000 hours at 25°C
 Weight: 1300 g

Bearing system

BALL	SLEEVE
●	●

Available Functions

FG	PWM	RD	LD
●	●	●	●

MODEL	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximun Air Flow		Maximun Air Pressure		Noise
PART NO.	VDC	VDC	Amp	Watt	R.P.M	m3/min	CFM	mmH2O	INH2O	DB-A
MFL22599D2-L	24	18 ~ 26.5	4.2	100.8	1500	639.6	376.7	45.4	1.78	37.9
MFL22599D2-M			5.5	132	2000	852.8	502.3	60.5	2.38	50.5
MFL22599D2-H			7	168	2800	1193.9	703.2	84.7	3.33	70.7
MFL22599D4-L	48	36 ~ 54	2	96	1500	639.6	376.7	45.4	1.78	37.98
MFL22599D4-M			2.8	134.4	2000	852.8	502.3	60.5	2.38	50.5
MFL22599D4-H			3.8	182.4	2700	1151.3	678.7	81.7	3.21	68.2

DIMENSIONS DRAWING & P&Q CURVE

